

14 60KW-80KW dual gun integrated DC charging pile



60KW-80KW integrated DC charging pile			
Basic index	Rated power	60KW	80KW
	Gun count	2 (250A)	
	Heat-dissipating method	Forced cooling	
	Background communication	LAN/4G	
	Operating environment	Indoor or outdoor (IP54)	
	Size (L*W*H)	700*400*1600mm	
Input characteristics	Weight (KG)	190 (Inclusion module)	220 (Inclusion module)
	Input voltage	380VAC±15%,Triphase+N+PE	
	Frequency	45Hz-65Hz	
	Rated input current	97A	129 A
	Power factor	≥0.99	
Output characteristics	Harmonic	≤5%	
	Voltage range	100-750VDC	
	Maximum current	Agun: 150A Bgun: 150A	Agun: 200A Bgun: 200A
	Charging strategy	40KW+20KW	40KW+40KW
	Peak efficiency	95%	
	Output voltage error	≤±0.5%	
	Input voltage error	≥30A , ≤±1%; <30A , ≤±0.3A	
	Voltage stabilization accuracy	≤±0.5%	
	Precision of steady current	≤±1%	
	Crest crest	≤±1%	
Environmental index	Operating temperature	-20 ~ +50°C	
	Storage temperature	-40 ~ +80°C	
	Relative humidity	5~90%RH,Condensation free	
	Altitude	The derating > 2000m is not required for 2000m. The operating temperature decreases by 1°C for every 100 m rise	